



Web Argentina



Web Uruguay



Web Paraguay

SPECIFICATION

S.N.	ITEMS & DESCRIPTION	IMAGE
	Mass Flow Meter CG-15	
	Specifications of sensor	
	Fluid temperature	-70~+160°C
	End connection	Nut, M32x1.5
	Vibrating tube	Stainless steel 316L
	Sensor housing	Stainless steel 304
	Splitter & flange	Stainless steel 304
	Ex-mark	Ex II 2G Ex ib IIC T6...T1 Gb
	Specifications of transmitter	
	Operating temp.	-30°C~+60°C
	RH	≤95%, non condensing
	Atmospheric Pressure	86~106 kPa
	Operating voltage	AC85~265V or DC12~24V
	Output	RS485 Modbus RTU, Pulse
	Ex-mark	Ex II 2G Ex db [ib] IIC T6...T1 Gb
1	Specifications of mass flow meter	
	Model No.	CG-15
	Max. flow rate	50kg/min
	Nominal diameter	15mm
	MWP.	25MPa
	Zero stability	0.12kg/h
	Repeatability	0,05 %
	Liquid accuracy	±0.2%
	Gas accuracy	±0.5%
	Temp. accuracy	±1°C ±0.5% of reading
	Density accuracy	±0.002g/cm3
	Rangeability	1:20
	Ingress protection	IP67
	Warranty	2-year
	Certificate	CE, ATEX
	Package size	445*370*405mm
	G.W.	12kgs

